

Rupert, Gibbon & Spider, Inc

Material Safety Data Sheet

Lumiere 3D All Colors

According to Regulation (EC) No 1907/2006

Revised
September 28, 2011

Section 1 Identification

Company:

Rupert, Gibbon & Spider, Inc.
PO Box 425
Healdsburg, CA 95448
USA

Company Emergency:

Telephone: 707-433-9577
Fax: 707-433-4906
Email: service@jacquardproducts.com

24 Hour Emergency Response Information:

CHEMTREC: 800-424-9300

Product or Trade Name: Lumiere 3D
Product Code Number: JDP0201-JDP1224
Date Effective: September 28, 2011 (most recent revision)
Chemical Family: Styrene Acrylic Latex
T.S.C.A Status: Compliance
Chemical Formula: N/A

Section 2 Composition/Information on Ingredients

<u>Name</u>	<u>CAS#</u>	<u>% by weight</u>
Isoparaffinic Solvent	64742-47-8	<1.1%
Propylene Glycol	000057-55-6	<1%
Diethylaminoethanol	100-37-8	<.1%
Ammonium Hydroxide	1336-21-6	<.07%

Section 3 Hazard Identification

Primary Routes of Entry: Eyes, skin, inhalation and ingestion.

Medical Conditions Aggravated by Exposure: None known.

Potential Health Effects:

Eye Contact: May cause slight irritation.

Skin Contact: May cause slight irritation.

Ingestion: May cause slight irritation to mouth, throat and digestive system.

Inhalation: May cause slight irritation to throat, nose and lungs.

Chronic: None known.

Carcinogenicity: This product contains no ingredient listed as a carcinogen.

Rupert, Gibbon & Spider, Inc

Material Safety Data Sheet

Lumiere 3D All Colors

Section 4 First Aid Measures

Eye Contact: Flush with water for 15 minutes. Call physician if irritation occurs.

Skin Contact: Wash with soap and water.

Ingestion: To conscious person, give two glasses of water. Induce vomiting and call physician immediately.

Inhalation: Move person to fresh air.

Section 5 Fire-fighting Measures

Flash Point: None

Fire-fighting Instructions: Water for dried material. Use protective clothing and self-contained breathing apparatus.

Decomposition Products: Dried material may produce CO, CO₂, H₂O, N_xO, and other products from the burning of aliphatic/aromatic hydrocarbons.

Section 6 Accidental Release Measures

Steps to be taken if Material is Released or Spilled: Dispense sand, sawdust or vermiculite. Collect and place in waste container. Wash area thoroughly with water.

Section 7: Handling and storage

Handling: Use good hygienic practices (wash hands before eating, using bathroom or smoking). Under normal handling conditions, the risk of exposure to residual monomer is negligible. Monomer vapors can be generated when a product is heated during processing operation. Maintain adequate ventilation where product is heated or cured. Acrylic monomers can be detected by odor at a level far below existing or suggested work place exposure limits. Therefore, odor is not an induction of exposure problem or toxicity.

Storage: Store above 40°F.

Section 8: Exposure controls and personal protection

Personal Protective Equipment:

Eye/Face Protection: Wear splash goggles if contact with material is likely.

Skin Protection: Wear gloves if contact with material is likely.

Respiratory Protection: Not normally required with good ventilation.

Engineering Controls: Normal room ventilation.

Section 9: Physical and chemical properties

Boiling Point: 212°F

Specific Gravity (water=1): 1.0

Vapor Pressure: Same as water.

Vapor Density (air=1): Same as water.

% Volatile by weight: 50

pH: 8.0

Appearance and Odor: Variety of pearlescent and metallic colors with an acrylic odor.

Rupert, Gibbon & Spider, Inc

Material Safety Data Sheet

Lumiere 3D All Colors

Section 10: Stability and reactivity

Chemical Stability: Stable.

Polymerization: Will not occur.

Conditions to Avoid: None known.

Hazardous Decomposition Products: None.

Section 11: Toxicological information

Acute: This formulation has not been tested for acute toxicity. It is expected to have a low odor of acute oral toxicity. The formulation contains a surfactant which has been reported to be a skin and eye irritant.

Chronic: This material has not been identified as a carcinogen by NTP, IARC or OSHA. Total monomer content does not exceed 0.1%. Use of this product may, in some circumstances, generate the same hazards associated with the monomers. The user should evaluate use to determine if hazards from residual monomer exist. Chronic health effects would not be expected as long as good industrial hygiene and proper safety precautions are provided.

Section 12: Ecological information:

No information available.

Section 13: Disposal considerations

Dispose of in accordance with federal, state and local regulations.

Section 14: Transport information

For domestic transportation purpose, this product is not designated as a hazardous material by the US Department of Transportation.

Section 15: Regulatory information

TSCA: This product is listed with TSCA

SARA Title III:

Section 311 and 312 Health and Physical Hazards:

Immediate	Delayed	Fire	Pressure	Reactivity
[]	[]	[]	[]	[]

Volatile Organic Compounds: 0.1% or <0.01 pounds/gallon.

Butyl Acrylate <.05%

Styrene <.05%

Hazardous Air Pollutants: Styrene <.05%

Canada:

WHMIS: This product has been prepared in compliance with Controlled Product Regulations.

Controlled Product Hazard: Class D, Division 2, Subdivision B.

Rupert, Gibbon & Spider, Inc

Material Safety Data Sheet

Lumiere 3D All Colors

Ingredients which may require reporting under the WHMIS IDL are: None.

Canadian Environmental Protection Act: All components are on the Domestic Substance List (DSL).

Section 16: Other information

HMIS Rating: Health=1, Flammability=1, Reactivity=0, Personal Protective Equipment=B,
Hazard Rating Scale: 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe

Notice to Reader

The information contained in this MSDS is based on data from sources considered to be reliable but Rupert, Gibbon & Spider Inc. does not guarantee the accuracy or completeness thereof. Rupert, Gibbon & Spider Inc. urges each customer or recipient of this MSDS to study it carefully to become aware of and understand the hazards associated with this product. The reader should consider consulting reference works or individuals who are experts in ventilation, toxicology or fire and understand the data in this MSDS.