


Cyanotype Kit





Start by only mixing together a small amount of **Cyanotype Sensitizer**. A little goes a long way and it is only stable for several hours once mixed.

6 Pour the Cyanotype Sensitizer into a *bowl or other container of your choice that will not be used for food consumption.






COATING SURFACES



** The Hahnemühle Platinum Rag Fine Art Paper provided is the best option for cyanotype.

You can explore limitless options for substrates, such as natural fabrics, wood, canvas, leather, and other porous or semi-porous surfaces.

In general, non-buffered rag papers with minimal external sizing work best. Test first when possible for best results.



Coated paper **may be stored** for use at a **later date**. Keep in a **dry**, **dark** place.



TIME TO PRINT!





Now it's time to


for your print!

curate the objects





Anything that **casts a shadow** is up for consideration!



OBJECT BASED PRINTS



Place objects onto the coated paper, then expose to sunlight for 10 - 20 minutes or until the exposed areas of the print turn bronze.

CONTINUED ON STEP


















IMPORTANT:

The film will only accept ink on

one side. Pinch a corner of the film with moistened fingers and **only** print on the side that feels

sticky!



To create a film negative, first edit vour image using software or our website, and then use your home printer to print the negative onto the provided SolarFast Film.




Make the photo black and white and then invert it to negative.





CAUTION: Check your printer instructions for proper page loading instructions



CONTINUED ON STEP













The film will only accept ink on one side. Pinch a corner

of the film with moistened fingers and only draw on the side that feels sticky!



Draw directly on the film using the provided Film Marker. You can make an edition of countless cyanotype prints from your drawing!




USING THE CONTACT PRINTING FRAME













Place the film negative OR drawing on top of the coated paper between the glass and backer board to keep it rigid and flush.



Use the **provided clips** to pinch the contact-printing frame tight.

Expose to sunlight for **10 - 20** minutes or until the exposed areas of the print turn **bronze**.

RINSING & DRYING YOUR PRINT!



Rinse the exposed print in water for at least 5 minutes, changing the water periodically until it runs clear.


* OPTIONAL

If you want to skip the
24 - 48 hour wait it is possible to
reach the final tonal depth
instantaneously by adding a drop
of Hydrogen

Peroxide to the final rinse bath.
Afterward, rinse one

last time.





Enjoy your print!